

POWER ACE Schmalkeilriemen / POWER ACE Narrow V-belts

3V		5V		8V	
Abmessung Dimension	Außen-länge Outside length [mm]	Abmessung Dimension	Außen-länge Outside length [mm]	Abmessung Dimension	Außen-länge Outside length [mm]
3V 250	635	5V 500	1.270	8V 1000	2.540
3V 265	673	5V 530	1.346	8V 1060	2.692
3V 280	711	5V 560	1.422	8V 1120	2.845
3V 300	762	5V 600	1.524	8V 1180	2.997
3V 315	800	5V 630	1.600	8V 1250	3.175
3V 335	851	5V 670	1.691	8V 1320	3.353
3V 355	902	5V 710	1.803	8V 1400	3.556
3V 375	953	5V 750	1.905	8V 1500	3.810
3V 400	1.016	5V 800	2.032	8V 1600	4.045
3V 425	1.080	5V 850	2.159	8V 1700	4.318
3V 450	1.143	5V 900	2.286	8V 1800	4.572
3V 475	1.207	5V 950	2.413	8V 1900	4.826
3V 500	1.270	5V 1000	2.540	8V 2000	5.080
3V 530	1.346	5V 1060	2.692	8V 2120	5.385
3V 560	1.422	5V 1120	2.845	8V 2240	5.690
3V 600	1.524	5V 1180	2.997	8V 2360	5.994
3V 630	1.600	5V 1250	3.175	8V 2500	6.350
3V 670	1.702	5V 1320	3.353	8V 2650	6.731
3V 710	1.803	5V 1350	3.429	8V 2800	7.112
3V 750	1.905	5V 1400	3.556	8V 3000	7.620
3V 800	2.032	5V 1500	3.810	8V 3150	8.001
3V 850	2.159	5V 1600	4.064	8V 3350	8.509
3V 900	2.286	5V 1700	4.318	8V 3550	9.017
3V 950	2.413	5V 1800	4.572	8V 3750	9.525
3V 1000	2.540	5V 1900	4.826	8V 4000	10.160
3V 1060	2.692	5V 2000	5.069	8V 4250	10.795
3V 1120	2.845	5V 2120	5.385	8V 4500	11.430
3V 1180	2.997	5V 2240	5.690	8V 4750	12.065
3V 1250	3.175	5V 2360	5.994	8V 5000	12.700
3V 1320	3.353	5V 2500	6.350		
3V 1400	3.556	5V 2650	6.731		
		5V 2800	7.112		
		5V 3000	7.620		
		5V 3150	8.001		
		5V 3350	8.509		
		5V 3550	9.017		

Lieferzeiten und Mindestabnahmen auf Anfrage. / Deliveries and min. order quantities on request.